

NETSYSTEM

Onduleur 450VA ~ 2.2 kVA INLINE Rackable

NS2R 600VA-2KVA
PF 0.6




Features

- LED display or LCD display selectable
- Microprocessor-based digital control
- Boost and buck AVR for voltage stabilization
- Auto sensing frequency
- Wide input voltage range
- Power-on self test
- Cold start
- Auto restart when mains power is restored
- Auto track mains phase to ensure that inverter output voltage has same phase with utility voltage, reducing transfer time and peak surge
- Intelligent battery management: battery temperature compensation to extend the battery life; three-stage charging to shorten recharge time
- Short circuit, battery overcharge / overdischarge, overload, surge protections
- Automatic charging in OFF mode
- Optional no-load shutdown
- Optional RS232 / USB communication port and RJ11 / RJ45 protection
- Unattended safety shutdown: system alarm and auto Power-On / Off by RS232 or USB interface communicating with PC

Rear Panel

1. Output Outlets (selectable)
2. TEL/Modem/Fax surge protection (optional)
3. USB (optional)
4. AC Input



Distribué par : IPSYSTEME GROUPE.

El EULMA : Tel 0661334933/ 0542227394 / 0776200442 - Tel fax 036762083 - Viber 0661334933 Email : iipsysteme@gmail.com

El HAMIZ : Tel 0657181903 - Viber 0657181903 - Email : magtech@gmail.com.

Specifications:

MODEL		NS245RTS	NS265RTS	NS265RTS	NS2120RTS	NS2120RTS	NS2200RTS
Capacity		450 VA 270 W	650 VA 390 W	850 VA 510 W	1200 VA 720 W	1500 VA 900 W	2200 VA 1320 W
INPUT							
Voltage		100 V / 110 V / 120 V: 80 ~ 150 Vac; 220 V / 230 V / 240 V: 162 ~ 295 Vac (220 V: 145 ~ 295 Vac optional)					
Frequency		50 / 60 Hz ± 10% (auto-sense)					
OUTPUT							
Voltage		100 V / 110 V / 120 Vac ± 10% or 220 V / 230 V / 240 Vac ± 10%					
Frequency		50 / 60 Hz ± 1% (auto-sense)					
Waveform		Mains mode: pure sine wave ; battery mode: simulated sine wave					
Transfer time		Typical 2 ~ 7 ms; Max.10 ms					
BATTERIES							
DC voltage		12 V			24 V		
Configuration		12 V / 4.5 Ah × 1	12 V / 7.0 Ah × 1	12 V / 8.0 Ah × 1	12 V / 7.0 Ah × 2	12V / 8.0 Ah× 2	12 V / 9.0 Ah× 2
Recharge time		6 ~ 8 h					
COMMUNICATIONS							
USB / RS232 / SNMP (optional)		Supports Windows® 98 / 2000 / 2003 / XP / Vista / 2008 / Windows®7 / 8 / 10					
OTHERS							
Protections		Short circuit - battery overcharge – overdischarge – overload - surge					
Humidity		20 ~ 90% RH @ 0 ~ 40℃ (non-condensing)					
Noise level		≤ 45 dB (1m)					
Plastic case	Net / Gross weight (kg)	3.8 / 4.3	4.3 / 4.8	5.3 / 5.8	9.5 / 10.0	10.7 / 11.2	/
	Dimensions (W×D×H) (mm)	100×280×140			140×345×170		/
	Packaged dimensions (W×D×H) (mm)	139×325×210			198×406×245		/
	Quantity / 20ft	2300 pcs			1000 pcs		/
Metal case	Net / Gross weight (kg)	/	5.5 / 6.0	6.7 / 7.2	10.5 / 11.2	12.6 / 13.4	14.0 / 14.8
	Dimensions (W×D×H) (mm)	/	95×320×160		125×320×225		125×380×225
	Packaged dimensions (W×D×H) (mm)	/	145×375×230		180×390×295		180×450×295
	Quantity / 20ft	/	2000 pcs		1000 pcs		
Rack mount	Net / Gross weight (kg)	/	7.8 / 8.3	9.0 / 9.5	12.6 / 13.2	15.7 / 16.3	17.0 / 17.6
	Dimensions (W×D×H) (mm)	/	308×438×88		308×438×132		
	Packaged dimensions (W×D×H) (mm)	/	395×525×185		395×525×225		

Distribué par : IPSYSTEME GROUPE.

El EULMA : Tel 0661334933/ 0542227394 / 0776200442 - Tel fax 036762083 - Viber 0661334933 Email : iipsysteme@gmail.com

El HAMIZ : Tel 0657181903 - Viber 0657181903 - Email : magtech@gmail.com.